



3.3 MAX AIR II COMPRESSOR

PRODUCT INFORMATION SHEET

"High Volume, High Quality 12 Volt Air Compressor"



SPECIFICATIONS

| | |
|-------------|---|
| Part Number | 55X13 |
| Materials | Cast Alloy air pump casing with cooling fins Cast Air Filter Diamond Plate Base Tray |
| Dimensions | Unit: 300mm (L) x 210mm (H) x 140mm (W) |
| Capacity | <ul style="list-style-type: none"> • Air Flow : 72 litres per minute • Maximum Draw: 30A Fused • Max. Ambient Temp: 60 DegC • Max. Duty Cycle: 40 mins @ 40 psi @ 24 DegC • Max. Voltage: 13.8V • Max Pressure: 150 psi • Thermal Cut out switch |
| Weight | 5.2 kg |
| Warranty | 5 Year No-Fuss Warranty |

VEHICLE APPLICATIONS

Specially designed for high flow pumping large 4x4 tyres and truck tyres.

PRODUCT TIPS

- Supplied with 3 additional nozzles. Handy for inflating footballs, basketballs, bicycle tyres etc.
- Robust Carry/Storage bag with additional pockets for extra items included.
- Removable rubber-mounted base-plate to disperse vibrations.
- Supplied with hard mount kit to permanently mount compressor, dry sump allows mounting on any angle.
- Built in tyre deflation valve for controlled deflation

...Continued over page



3.3 MAX AIR II COMPRESSOR

PRODUCT INFORMATION SHEET

"High Volume, High Quality 12 Volt Air Compressor"

SAFETY PRECAUTIONS

- Keep engine idling while inflating tyres to avoid unnecessary battery draw.

| FEATURES | BENEFITS |
|----------|----------|
|----------|----------|

| | |
|--|---|
| Powerful 12 volt motor and air pump, delivering 72 litres per minute | Fast and reliable portable compressed air at an affordable price |
| Rubber Mounted Base-plate removable for hard mount applications | Allows dispersion of vibrations without damaged to the compressor, keeps unit clean |
| Quality manufactured and accredited to International ISO9002 Standards | Reliable high quality performance |
| 4.5 metre power lead and inline fuse for compressor protection | 7.5 metre coiled air hose with gauge at the tyre end of hose. |
| Built-in on-off switch | Built in Tyre Deflation valve for controlled deflation |
| Automatic Thermal Cut-off switch | Protects motor against damage from overheating |
| Direct Battery clamps with an in-line fuse, <u>not</u> a cigarette lighter connection | No voltage drop or blown fuses in vehicle's fuse box, easy and simple to use |
| Essential 4WD equipment after lowering your vehicle's tyre pressure to drive in sand, mud or rocky terrain | Robust carry/storage bag for compressor protection and storage |

ACCESSORIES / SPARE PARTS

- 7.5 Metre (25ft) extension Coil air hose.....(Part Number: 55X08)
- Replacement Air Filters (Pack of 5).....(Part Number: 55X18)
- Replacement Alloy Air Filter Casing.....(Part Number: 55X17)
- Replacement coil air hose with gauge.....(Part Number: 55X21)