



4.2 DRAG CHAINS PRODUCT INFORMATION SHEET

"Don't go bush without Bushranger 4WD Recovery Gear"



Quality
Endorsed
Company
ISO 9001:2008
SAI Global



- Available in both **5 meter** and **8 meter** lengths
- All components tested to AS4344:2001
- Lashing Capacity (Straight Line): 3,800kg
- Lashing Capacity (Looped): 2,850kg
- Drag Chains are supplied with a Master Link on one end and a Grab Hook on the other end
- Material Grade: G70
- 8mm Chain Links
- Robust Carry Bag
- 5 Year 'No-Fuss' Warranty

SPECIFICATIONS

Part Number	58X10
Description	5m Drag Chain with Carry Bag
Dimensions	8mm Chain Links x 5 meters
Weight	8kg

Part Number	58X11
Description	8m Drag Chain with Carry Bag
Dimensions	8mm Chain Links x 8 meters
Weight	13kg

PRODUCT TIPS

- Ensure the chain and components are free of any wear.
- Ensure the chain is evenly loaded in use.
- Ensure the chain is free of twists and is protected from any sharp corners.
- Do not tie knots in the lashing chain.
- Do not join with wire bolts or with joining links.
- Avoid the possibility of crushing the chain under the load.
- When the chain is tensioned ensure the force applied does not exceed the manufacturer's recommendations.

...Continued over page



4.2 DRAG CHAINS PRODUCT INFORMATION SHEET

"Don't go bush without Bushranger 4WD Recovery Gear"



CARE & MAINTENANCE

- Never heat or heat-treat the lashing chain or components.
- Lightly oil the chain and components prior to prolonged storage.
- Store chain and components in a clean, dry place.

INSPECTION & SAFETY PRECAUTIONS

- Prior to each use, the chain and components shall be visually inspected to ensure it is free of any damage or wear. If necessary clean before they are inspected.
- Every chain link and component should be individually inspected for signs of wear, twisting, stretching, nicks or gouging.
- If any defects are detected, the chain and components shall immediately be withdrawn from service until repaired.
- Any damaged chain or components which cannot be repaired should be discarded.