



7.1 BUSHPAK

PRODUCT INFORMATION SHEET

"Complete protection for all your Roof Rack Luggage"



SPECIFICATIONS

Part Numbers	Small	- 64X10
	Medium	- 64X11
	Large	- 64X12
Materials	Seam welded reinforced PVC	
Dimensions	Small	- 865mm x 1020mm x 330mm
	Medium	- 1180mm x 980mm x 330mm
	Large	- 1220mm x 1520mm x 330 mm
Weight	Small	- 2.4kg
	Medium	- 2.8kg
	Large	- 3.4kg
Warranty	5 Year No-Fuss Warranty	

VEHICLE APPLICATIONS

Ideal for use in basket type Roof Racks, Station Wagon Roof Racks or with Bar type Roof Racks.

PRODUCT TIPS

- Never store BushPAK away when wet. Always allow to fully dry out before storing to prevent mildew.
- Ensure BushPAK is securely fastened down to the vehicle's roof rack before driving

Warranty

Bushranger BushPAK is covered by a Five Year No-Fuss Warranty against material and manufacturing faults, which means that this product will perform to your satisfaction for a minimum of five years, excluding:

- ❑ Accidental or malicious cuts or holes in the fabric
- ❑ Wear and tear, including all abrasion to the fabric, broken buckles, worn or broken zippers



7.1 BUSHPAK

PRODUCT INFORMATION SHEET

"Complete protection for all your Roof Rack Luggage"

FEATURES	BENEFITS
Super tough seam welded reinforced PVC to keep your luggage completely protected	Peace of mind while you travel knowing your roof top luggage is fully secure
After use, simply fold and store in its compact box	No bulky storage problems
Easy to adjust tie down straps at each corner and centre rear. The large and medium sack also has centre straps on both sides	Attaches easily to the roof rack
Non-slip self locking buckles that come with a keeper	Buckles stay tight and the tail end is secured against flapping
All seams are PVC welded	For extra strength and durability
Large continuous zipper around both sides and rear	Makes loading and unloading a breeze.
Zipper has double slides	Can be padlocked together
Velcro tabs at each bottom corner	Holds the Rack Sack out in position for easier loading
Zipper is covered by a large flap and held down by velcro tabs	Prevents water entry through the teeth of the zipper

FITTING INSTRUCTIONS (Included in Product Packaging)

1. Always face the non-zippered end of the BushPAK forward for travelling to minimise the risk of water being blown under the flap and through the zipper.
2. BushPAK comes with four Velcro corner tabs so it can be held out in place for easy loading. These tabs are not for securing the Rack Sack to the Roof Rack when it is fully loaded.
3. Care must be taken to ensure the BushPAK is fully strapped down and secure on your vehicle's roof before driving.
4. Care must also be taken to avoid abrasion of the vehicle or the BushPAK through flapping or other movement. Always attempt to completely fill/extend your BushPAK to prevent this from occurring.
 - **Note:** If the BushPAK is mounted directly on the roof of the vehicle and secured between two roof bars there is a risk of damage to the vehicle by abrasion or denting.
 - It is recommended that if the BushPAK is in direct contact with the vehicle's roof, only use it for shorter trips with soft loads only.
5. BushPAK must be fully dried before folding and storing away.
6. BushPAK can be mounted and removed fully laden, if desired for security reasons or for ease of packing in certain circumstances.

HANDY "TIP": Heavy items can quickly wear a hole in the fabric if in direct contact with Rack Sack during a long trip. We suggest you wrap such items in felt or similar cloth to avoid unwarranted wear.

Please note that the colour of the PVC will fade after prolonged exposure to sunlight. This is normal